PRODUCT SHEET

Badge or smartphone: secure reading, no compromise.

HID Global

HID Signo 40T mechanical keypad reader - 13.56 MHz and 125 kHz, NFC/BLE, OSDP/Wiegand

SCAP part number: 40T



HID Signo 40T reader with mechanical keypad, wide, wall switch format. Its mechanical keys give clear feedback under the finger: it suits harsh environments, cold, wet conditions and gloved hands.

Key features

- Mechanical keypad: clear feedback on every press, usable with gloves or in low visibility
- Designed for harsh environments, in cold or wet weather
- Mobile-ready: reads cards, fobs and smartphone credentials
- Reads 13.56 MHz and 125 kHz cards
- OSDP or Wiegand link to the controller

Applications

- Outdoor access points exposed to cold and damp
- Sites where users wear gloves
- Sites that require a mechanical keypad



Technical specifications

HID model	Signo 40T, mechanical keypad
Cards read at 13.56 MHz (NFC)	Seos, iCLASS SE, iCLASS, MIFARE DESFire EV1, EV2 and EV3, MIFARE Classic
Cards read at 125 kHz	HID Prox, Indala Prox, Dorado Prox and EM Prox (Standard and Custom profiles)
Interfaces	OSDP, Wiegand
Dimensions	80 × 122.5 × 22.5 mm
Mounting	Wall switch format
Manufacturer's warranty	Limited lifetime (HID terms)
Note	The profile is not specified in this part number: it determines which technologies are read. Contact us to confirm compatibility.
Keypad	Yes
Housing width	Wide
Secure reading	Yes: Seos and iCLASS (DESFire badges require a Standard or Custom profile)
Bluetooth	Yes

Indicative specifications, subject to change without notice. Prices and availability: contact SCAP.