HID Global

Dual-interface reader - Omnikey - 13.56 MHz

SCAP part number: 5422

HID OMNIKEY desktop reader for reading and encoding cards (USB).



Key features

- USB connection
- HID Global OMNIKEY range

Technical specifications

Range	HID OMNIKEY
Interface	USB
Frequency	13.56 MHz

Applications

- Badge enrolment and encoding
- Workstation authentication

Commercial information

SCAP part number	5422
Brand	HID Global – OMNIKEY range
Family	OMNIKEY brand
Description	Dual-interface reader - Omnikey - 13.56 MHz
Delivery	Constant stock; next-day or two-day delivery depending on availability. Lead times are given for guidance only.
Free carriage threshold	For any order delivered in a single shipment with a minimum value of €1,000 excl. VAT (excluding carriage). Mainland France.
Minimum order	€100 excl. VAT. Below that: payment in advance or a €15 excl. VAT handling charge.
Payment	First order paid in advance when the account is opened, then 30 days end of month once credit insurance is approved.
Warranty	12 months from the invoice date (return for replacement or repair of the faulty part).

Complaints	Visible defects: reservations within 2 clear days of receipt. Quantities and quality: 8 clear days.
Returns	Only with prior written agreement, within one month of delivery; credit note issued on the basis of 90% of the invoiced amount.

Documents and sources

- Data source: SCAP description; HID OMNIKEY data sheets

Indicative specifications, subject to change without notice. Prices and availability: contact SCAP.