ROSSLARE

Dual-band QR code reader 125 kHz / 13.56 MHz, AY-H30QR

SCAP part number: AY-H30QR

Version of the dual-band QR code reader (green colour).



Key features

- Current Rosslare Security Products range
- Manufacturer data sheet available

Technical specifications

Range	Rosslare
Reading	QR code, 2D barcode, 125 kHz and 13.56 MHz
Output	Wiegand
Protection rating	IP65
Frequency	13.56 MHz + 125 kHz
Interfaces / protocols	QR code reading
Housing width	Wide
QR code	Yes

Applications

- Access control

Commercial information

SCAP part number	AY-H30QR
Brand	ROSSLARE – current Rosslare range
Family	ROSSLARE brand
Description	Dual-band QR code reader 125 kHz / 13.56 MHz, AY-H30QR
Delivery	Constant stock; next-day or two-day delivery depending on availability. Lead times are given for guidance only.

Free carriage threshold	For any order delivered in a single shipment with a minimum value of €1,000 excl. VAT (excluding carriage). Mainland France.
Minimum order	€100 excl. VAT. Below that: payment in advance or a €15 excl. VAT handling charge.
Payment	First order paid in advance when the account is opened, then 30 days end of month once credit insurance is approved.
Warranty	12 months from the invoice date (return for replacement or repair of the faulty part).
Complaints	Visible defects: reservations within 2 clear days of receipt. Quantities and quality: 8 clear days.
Returns	Only with prior written agreement, within one month of delivery; credit note issued on the basis of 90% of the invoiced amount.

Documents and sources

- Manufacturer data sheet (PDF)
- Data source: Rosslare Security Products manufacturer website (rosslaresecurity.com), data sheets

Indicative specifications, subject to change without notice. Prices and availability: contact SCAP.