ICC

Multi-technology reader 13.56 MIFARE®/DESFIRE® CSN - 125 EM/TEMIC/HID

SCAP part number: RE3T

ICC multi-technology reader with two antennas, 125 kHz and 13.56 MHz. It reads EM, TEMIC and HID Prox badges, as well as the serial number (CSN) of MIFARE® and DESFire® badges.



Key features

- Two antennas: 125 kHz and 13.56 MHz in the same reader
- Reads 125 kHz EM, TEMIC and HID Prox badges
- Reads the serial number (CSN) of MIFARE® and DESFire® badges
- Lets several badge populations coexist on the same site

Technical specifications

Frequencies	125 kHz and 13.56 MHz (two antennas)
Technologies read at 125 kHz	EM, TEMIC, HID Prox
Technologies read at 13.56 MHz	MIFARE® and DESFire® serial number (CSN)
Secure reading	No: serial number reading only, without an encryption key
Housing width	Narrow

Applications

- Sites equipped with 125 kHz and 13.56 MHz badges
- Sites with low security stakes

Commercial information

SCAP part number	RE3T
Brand	ICC
Family	ICC brand
Description	Multi-technology reader 13.56 MIFARE®/DESFIRE® CSN - 125 EM/TEMIC/HID
Delivery	Constant stock; next-day or two-day delivery depending on availability. Lead times are given for guidance only.

Free carriage threshold	For any order delivered in a single shipment with a minimum value of €1,000 excl. VAT (excluding carriage). Mainland France.
Minimum order	€100 excl. VAT. Below that: payment in advance or a €15 excl. VAT handling charge.
Payment	First order paid in advance when the account is opened, then 30 days end of month once credit insurance is approved.
Warranty	12 months from the invoice date (return for replacement or repair of the faulty part).
Complaints	Visible defects: reservations within 2 clear days of receipt. Quantities and quality: 8 clear days.
Returns	Only with prior written agreement, within one month of delivery; credit note issued on the basis of 90% of the invoiced amount.

Indicative specifications, subject to change without notice. Prices and availability: contact SCAP.